

3MP StereoVision People Counting Camera

Dual-sensor H.265 IR Network Camera



System Overview

The Dahua 3MP Dual-lens People Counting Camera offers Artificial Intelligence at the edge – using complex real-time people counting algorithms to deliver accurate flow statistics. The camera uses an advanced Vision Processor Unit (VPU) that delivers high-performance machine vision and visual awareness that enables advanced vision applications that are impossible with conventional ISPs.

The dual 3 MP sensors work in combination to deliver a single video stream that captures 3D depth in the image, offering improved accuracy as compared to single-sensor cameras. The dual-sensor technology captures an object's height, letting the camera better distinguish between people and other objects.

The camera offers two distinct people counting functions, Line Crossing and Regional. The line crossing function counts the number of people crossing a defined lines, and offers maximum/minimum height detection to help filter objects that are too tall or too small. The Regional function counts the number of people in ten (10) distinct, user-defined regions.

Functions

Intelligent Video System (IVS)

IVS is a built-in video analytic algorithm that delivers intelligent functions to monitor a scene for motion detection and a dramatic scene change and generate a warning message to inspect the camera. A camera with IVS quickly and accurately responds to monitoring events in a specific area. The DH-IPC-HDW8341XN-3D offers advanced people counting algorithms that offer built-in calibration and function dual-lens design for depth of information and accurate people counting.

Smart Scene Adaptive Technology

Smart Scene Adaptive (SSA) is an intelligent image technology, developed by Dahua that automatically evaluates and compensates for changes in the luminance of a scene. SSA automatically regulates the exposure parameters to improve image quality in a backlit scene, especially in scenes with traffic lights or headlights.

- Two (2) 1/2.8-in. 3 MP Progressive-scan CMOS Sensors
- Triple-stream Encoding
- Smart H.265+ and Smart H.264+ Dual Codecs
- 3 MP (2048 x 1536) at 25 fps; 2.8 mm Fixed Lens
- Advanced, Accurate People Counting: Supports Line Crossing and Regional People Counting
- ArcticPro Series Camera - Operational down to -40°C (-40°F)
- IP67 Ingress Protection
- True Day/Night IR Cut Filter
- Built-in Microphone
- Maximum IR Length 10 m (33 ft)
- Intelligent Video System with Advanced Business Analytics
- Five-year Warranty*



Intelligent Business Analysis

The built-in IVS features people counting and heat map functionality, advanced features that add business intelligence to your security system. Intelligent Analysis tracks and stores daily, weekly, monthly, and yearly people flow through a defined scene and produces a configurable report. The system uses this data to produce a Heat Map, a two-dimensional representation of data that provides an immediate visual summary of information. People Counting and Heat Maps can identify the most active areas of a retail space providing valuable data analysis for commercial applications.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

ArcticPro

The Dahua ArcticPro Series of extreme-environment cameras combine temperature-tolerant components with a waterproof enclosure to ensure flawless operation in temperatures as low as -40°F (-40°C) without the need for an internal heater. The lack of a heater reduces the camera's power consumption and saves operating costs. For applications that demand high-resolution video with advanced features in extremely cold environments, the Dahua ArcticPro Series offers a camera to satisfy the most demanding requirements.

Environmental

Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications.

Technical Specification

Camera

Image Sensor	Two (2) 1/2.8-in. 3 MP CMOS Sensors
Effective Pixels	2048 (H) x 1536 (V)
RAM/ROM	512 MB/4096 MB
Scanning System	Progressive
Minimum Illumination	Color: 0.009 lux at F1.8 (1/3 s, 30 IRE) Color: 0.08 lux at F1.8 (1/30 s, 30 IRE) 0 lux at F1.8 (IR on)
S/N Ratio	More than 50 dB
IR Distance	10.0 m (32.81 ft)
IR On/Off Control	Auto, Manual
IR LEDs	One (1)

Lens

Lens Type	Fixed				
Mount Type	Board-in				
Focal Length	2.8 mm, each lens				
Maximum Aperture	F1.8				
Angle of View	Horizontal: 137° Vertical: 114°				
Focus Control	Fixed				
Close Focus Distance	0.6 m (1.97 ft)				
DORI Distance ¹	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	45 m (147 ft)	18 m (59 ft)	9 m (29 ft)	4 m (13 ft)

Detection Width

Installation Height	2.20 m	2.50 m	2.80 m	3.50 m
Detection Width	1.10 m	2.60 m	3.10 m	4.30 m

Pan/Tilt/Rotation

Range	Tilt: -10° to 70°
-------	-------------------

Video

Compression	H.265, H.264H, MJPEG (Sub Stream only)
Smart Codec ²	Smart H.265+, Smart H.264+
Streaming Capability	Three (3) Streams
Resolution	3 MP (2048 x 1536), 1080p (1920 x 1080), 1.3 MP (1280 x 960), 720p (1280 x 720), D1 (704 x 480), VGA (640 x 480), CIF (342 x 240)
Frame Rate	Main Stream: 3 MP at 25 fps
	Sub Stream 1: D1 at 25 fps
	Sub Stream 2: 6 MP at 7 fps (for camera adjustment only)

Bit Rate Control	CBR, VBR
Bit Rate	H.264: 2560 kbps to 10240 Kbps H.265: 1024 kbps to 8704 Kbps
Day/Night	Auto (ICR), Color, B/W
BLC Mode	HLC, BLC, Digital WDR
White Balance	Auto, Natural, Street Lamp, Outdoor, Manual, Regional Custom
Gain Control	Auto, Gain Priority, Shutter Priority, Manual
Noise Reduction	3D DNR
Motion Detection	Off, On (4 Zones, Rectangular)
Region of Interest	Off, On (4 Zones)
Advanced Features	Smart IR Defog
Digital Zoom	16x
Privacy Masking	Off, On (4 Areas, Rectangular)

Audio

Compression	G.711a, G.711Mu, AAC, G.726
-------------	-----------------------------

Network

Ethernet	RJ-45 (100/1000 Base-T)
Protocol	HTTP, HTTPS, TCP, ARP, RTSP, RTP, RTCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/V6, QoS, UPnP, NTP, Bonjour, IEEE 802.1X, Multicast, ICMP, IGMP, TLS
Interoperability	ONVIF Profile S/G, API
Streaming Method	Unicast, Multicast
Max. User Access	10 Users/20 Users
Edge Storage	Network Attached Storage (NAS) Local PC for Instant Recording Micro SD Card, maximum 128 GB
Web Viewer	IE
Management Software	SmartPSS, DSS, DMSS
Mobile Operating System	IOS, Android

Certifications

Safety	EN 60950:2000 UL 60950-1
Electromagnetic Compatibility (EMC)	FCC Part 15 Subpart B

Interface

Video Output	One (1) Port, BNC (for camera adjustment only)
Audio	Input: • Two (2) Channels, RCA • One (1) Built-in Microphone Output: One (1) Channel, RCA
Alarm	Input: Two (2) Channels Output: Two (2) Channels

1. The DORI distance is a measure of the general proximity for a specific classification to help pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4, the standard that defines the criteria for the Detect, Observe, Recognize and Identify classifications.

2. The Smart Codec feature and the People Counting / IVS features cannot be used simultaneously.

3. The Heat Map and the People Counting cannot be used at the same time, only one analytic feature can be used at a time.

Electrical

Power Supply	12 VDC, 1 A or PoE (802.3af, Class 0)
Power Consumption	< 12 W

Environmental

Operating Conditions	-40° C to +60° C (-40° F to +140° F) Less than 95% RH
Storage Conditions	-40° C to +60° C (-40° F to +140° F) Less than 95% RH
Ingress Protection	IP67

Construction

Casing	Metal
Dimensions	204.0 mm x 78.0 mm x 62.0 mm (8.03 in. x 3.07 in. x 2.44 in.)
Net Weight	0.80 kg (1.76 lb)
Gross Weight	1.09 kg (2.40 lb)

Artificial Intelligence- People Counting^{2 3}

People Counting	<ul style="list-style-type: none"> Built-in Calibration Function Dual-lens Design for Depth of Information
Line Crossing	<ul style="list-style-type: none"> Maximum/Minimum Height Detection Sensitivity Control
Regional	<ul style="list-style-type: none"> Counts Number of People in a Defined Area Ten (10) Separate Regions

Intelligence²

IVS triggers an alarm and takes a defined action for the following events:

Standard Features	<ul style="list-style-type: none"> Tampering with the camera. Error writing to an onboard Micro SD card. Error sending or receiving data over the network. Unauthorized access to the camera.
Premium Features	
Motion	An object moves through any part of the scene.
Advanced Features	
Heat Map ³	Generates a visual representation of activity.

Ordering Information

Type	Part Number	Description
People Counting Camera	DH-IPC-HDW8341XN-3D	3 MP Dual-sensor StereoVision People Counting Camera
Accessory, optional	DH-PFM321D-US	12 VDC, 1 A Power Adapter
Hardware Included		1 x Dual-sensor Camera 1 x Bottom Panel 1 x Quick Mounting Adapter 1 x Waterproof Ethernet Connector 4 x Self-tapping Screws 4 x Wall Anchors 1 x Torx Wrench 1 x Product CD 1 x Quick Start Guide 1 x Regulator Information Manual

Accessories

Optional:



DH-PFM321D-US
12 VDC, 1 A Power Adapter

Dimensions (mm/inch)

