

Elevator Master Access Controller



- Manages Up to Eight (8) Elevator Control Modules (DHI-VTM416)
- Supports TCP/IP, RS-485, and Wiegand Protocols
- Stores 1,000 Users and 200,000 Card-swipe Records
- Issues Alarms for Tampering, Intrusion, Timeout, Duress, Invalid Card, and Incorrect Password
- Supports Built-in RTC, Manual Time-fixing, and Automatic Time-fixing
- Enables Anti-passback and Multi-door Interlock to Control Traffic in High-security Applications
- Supports Watchdog Mechanism to Ensure Operation Stability

System Overview

The DHI-ASC2204C-H is a main controller to manage elevator control modules. The controller supports RS-485 and Wiegand interface allows for flexible reader integrations and web service can be used to configure sub-controllers. The controller can issue alarms in the case of events such as tampering, intrusion, timeout, duress, invalid card, and incorrect passwords.

Technical Specification

System

Main Processor	Dual-core ARM Cortex A9
Memory	256 MB

Network

Network	Two (2) RJ-45 (10/100 Base-T) Ports
Internet Protocol	IPv4, TCP, UDP, HTTP, HTTPS, DDNS, Register, NTP, DST
Interoperability	SDK, ONVIF Profile C, CGI
Management Systems	DSS Pro

Interface

RS-485	Four (4) Ports
Wiegand	Four (4) Wiegand Ports

Controls

Door Sensors	Four (4) Door Sensors
Exit Buttons	Four (4) Exit Buttons
Alarms	Eight (8) Alarms
Lock Control Channels	Four (4) Lock control Channels

Alarms

Input	Eight (8) Inputs
Output	Eight (8) Outputs

Peripheral Card Readers

RS-485	Four (4) Channel RS-485
Wiegand	Four (4) Channel Wiegand

Capacity

Card Holders	200,000
Users	1,000
Events	150,000

Functions

Unlock Modes	Card Swipe, Finger Print, Password, Remote
Combination Unlock	Combination of Card Swipe, Fingerprint, and Password
Access Control	Remote Verification, Block List/Allow List, Multi-door Interlock, Multiple Authentication
User Management	General, VIP, Guest, Patrol, Block List, Duress
Alarm Function	<ul style="list-style-type: none"> • Door Time-out Alarm • Intrusion Alarm • Duress • Tamper Alarm • Anti-passback
Schedule Settings	Period: 128 Groups Holiday: 128 Groups

Operations

Power Supply	Power Cable Not Included
Primary Voltage	AC85-AC264, 50/60Hz
Operating Temperature	-30° C to +60° C (-22° F to +140° F) Less than 95% RH
RTC	Support


Construction

Case Construction	Iron
Product Dimensions (W x D x H)	270.0 mm x 90.0 mm x 330.0 mm (8.26 in. x 4.56 in. x 1.14 in.)
Gross Weight	2.0 kg (4.4 lb)
Installation	Indoor Surface Mount

Order Information

Type	Part Number	Description
Elevator Controller	DHI-ASC2204C-H	Elevator Main Access Controller
Elevator Module	DHI-VTM416	Elevator Control Module

Dimensions



Application

