

16-port Managed PoE Switch

Layer 2 PoE Switch



- Layer 2 Managed PoE Switch
- Supports the IEEE802.3af, IEEE802.3at, and Hi-PoE Standards
- 240 W PoE Budget
- 250 m (820 ft) PoE Transmission
- PoE Management, PoE Setting/Event Statistics/Green PoE
- Search and Upgrade via Configuration Tool
- High Lightning Protection Design
- Non-blocking Video Transmission

System Overview

DH-PFS4218-16ET-240 is a dedicated PoE switch designed especially for the security industry. The PoE management function displays power control and real-time port consumption. The switch provides long-distance (250 m / 820 ft) PoE transmission and a port for Hi-PoE powered devices.

Technical Specification

Ethernet Ports	Two (2) 10/100/1000 Base-T (Combo Port) Two (2) 1000 Base-X (Combo Port) 16 - 10/100 Base-T (PoE Power Supply)
PoE Power Consumption	Ports 1 and 2: Hi-PoE (60 W), PoE+, PoE Maximum per Port: ≤ 30 W Total Power Consumption: ≤ 240 W
PoE Protocol	PoE (IEEE802.3af), PoE+ (IEEE802.3at), Hi-PoE
Switching Capacity	8.8 Gbps
Packet Forwarding Rate	5.36 Mpps
Power Requirements	100 VAC to 240 VAC
Working Temperature	-10° C to 55° C (14° F to 131° F)
Application Humidity	10% to 90%
Lightning Protection	Common Mode: 4 KV Differential Mode: 2 KV
Dimensions (W x D x H)	440.0 mm x 300.0 mm x 44.0 mm (17.32 in. x 11.81 in. x 1.73 in.)
Weight	3.51 kg (7.74 lb)

Service Specification

System	Username/Password: admin/admin
	IP Address: 192.168.1.110/24
PoE Budget	240 W
MAC Table Size	4K
VLAN	802.1Q Standard VLAN
Spanning Tree	STP, RTSP
Port Aggregation	Static Link Aggregation, LACP Protocol
Port Mirroring	Many-to-One Port Mirroring
DHCP	DHCP-client Support
Long Distance Mode	Power and Data Transmission Distance up to 250 m (820.21 ft)
Flow Control	Half-duplex based on back pressure type control
	Full Duplex based on PAUSE Frame
Security Features	IP+MAC Binding, based on port IEEE802.1x Port Authentication
System Maintenance	One-key Recovery, Updated Packet Upload, System Log
QoS	High and Low Priority, WRR, 802.1P, DSCP, Supports priority according to protocol
Network Management	Web (HTTP and HTTPS Protocols), SNMP V1/V2C/V3
PoE Management	PoE Setting (real-time port consumption)
	PoE Event Statistics
	Green PoE

Ordering Information

Type	Part Number	Description
PoE Switch	DH-PFS4218-16ET-240	Layer 2 16-port Managed PoE Switch
Accessories, Optional	PFT3950	1.25 GB, 850 nm, 500 m, LC, Multi-mode
	PFT3960	1.25 GB, 1310/1550 nm, 20 km, LC, Single Mode
	PFT3970	1.25 GB, 1550/1310 nm, 20 km, LC, Single Mode