

Smart Professional Surveillance System User's Manual

Version 2.00.0

Table of Contents

1. OVERVIEW AND ENVIRONMENT.....	1
1.1 Overview.....	1
1.2 SmartPSS Interface.....	1
2. LOGIN	3
3. DEVICES	5
3.1 Auto Search	5
3.2 Manually Add.....	6
3.3 Batch Import and Add Device	8
3.4 Modify IP.....	8
4. PREVIEW.....	11
4.1 Live ciew.....	11
4.2 E-Map.....	16
4.2.1 New Map.....	16
4.2.2 New Hot Zone	18
4.3 Config IVS Channel.....	20
4.4 Smart Track Config (Fisheye+Dome)	23
4.5 Smart Track Config (Dome+Fixed).....	25
4.6 PTZ	28
4.6.1 Preset	30
4.6.2 Tour.....	30
4.6.3 Scan.....	31
4.6.4 Pattern.....	31
4.7 Fisheye View Mode	32
5. TOUR & TASK	34
6. PLAYBACK	38
6.1 Playback.....	38

6.2	Playback Device Record	41
6.3	Export Device Record	41
6.4	Playback Device Picture	43
6.5	Export Device Picture	44
6.6	Playback Local Record	44
6.7	Export Local Record	45
6.8	Playback Local Picture	47
7.	LOG SEARCH	49
7.1	Search Client Log	49
7.2	Search Device Log.....	49
8.	SYSTEM CONFIG	51
9.	USER.....	54
9.1	Role Info	54
9.2	User	55
10.	DEVICE CONFIG	58
11.	EVENT CONFIG.....	61
11.1	Event Type	61
11.2	Event Alarm Link Config	63
11.2.1	Link Notice	63
11.2.2	Link Video	64
11.2.3	Link Alarm Output	66
11.2.4	Arm Time	67
11.3	Event View	68
12.	VIDEO WALL.....	69
12.1	Video Wall.....	69
12.2	Set Video Wall and Output	71
12.3	Scheme Tour on Video Wall.....	74

12.4	Playback on Video Wall	76
13.	PEOPLE COUNT	77
14.	HEAT MAP	80
15.	PC-NVR	81
15.1	Disk Manager	81
15.2	Channel Management	81
15.3	Set Record Plan	82
15.4	Version Info	83
15.5	Modify Port	84
15.6	Modify Password	85

Welcome

Thank you for using our Smart Professional Surveillance System (SmartPSS)!
This user's manual is designed to be a reference tool for operation of your system.
Here you can find detailed operation information about SmartPSS.

1. Overview and Environment

1.1 Overview

SmartPSS is an abbreviation for Smart Professional Surveillance System.

The software is to manage small quantity security surveillance devices. It releases with the device and does not support the products from other manufacturers. It has the following features:

- View real-time video of several camera channels.
- View the playback video files from various cameras.
- Support multiple scheduled arms to realize auto PC guard.
- Support e-map; you can clearly view and manage all device locations.
- Video wall preview.
- People count and heat map.
- Search and export log.

1.2 SmartPSS Interface

SmartPSS software interface includes 5 parts: function tab, system info, function list, shortcut, and help. See Figure 1-1.















Figure 1-1

No.	Name	Note
-----	------	------

1	Function tab	Open function in New tab by clicking  , you can open new tab.
2	Help	<ul style="list-style-type: none"> • click , switch user. • click , lock screen • click , go to config page • click , get help document • click , min page • click , max page • click , exit
3	System Info	 16:24:54 : show system time click  , CPU occupancy and condition
4	Shortcut	click  , quickly enter Event tab
5	Function list	Include preview, playback, event, video wall, people count, log, event setup, device manager, device config, PC-NVR, tour plan, user and heat map.

2. Login


Background

For PC where SmartPSS is installed.

Item	Requirements
OS	Windows 7 and higher.
CPU	Intel core i3 or higher.
Display card	Intel HD Graphics and higher.
Memory	2GB or higher.
Displayer Resolution	1024x768 or higher.

Steps



Step 1. Double click . See Figure 2-1.

Note:

Default username is admin, without password. Please set password at first time login.




Figure 2-1

Step 2. Enter username and password. Click login. See Figure 2-2.

Note:

- When you check remember password, you do not need to enter password again at next login. When you check both remember password and auto login, you can auto login at next login.
- After you add device, you can see homepage, see Figure 2-2.




Figure 2-2

3. Devices

Here you can add a single device or batch device via auto search. You also can config and operate device.

3.1 Auto Search

Step 1. In Devices, click Search.

Step 2. Set device segment and click Search. See Figure 3-1.

Note:

- Click Refresh, to refresh searched device.
- Check IP of devoce
- Check device IP you want to modify, click Modify IP to change IP. See Ch 3.4.











Figure 3-1

Step 3. Check device you want to add, click Add.

Step 4. Click OK. Login box pops up.

Step 5. Enter device username and password. Click OK. After you add device, click Cancel, so system shows device list added. See Figure 3-2.

- After device is added, you can view device name, IP/domain, type, model, port, channel number, online status, SN and operate device.
- After device is added, in Devices it auto shows device type tab, you can view added device here.
- For different devices, please note that interface subject to actual interface.
 - ✧ Click  of device, to modify device info.
 - ✧ Click  of device, to go to device config page.
 - ✧ Click  of device to exit device. When icon changes to , click  again to re-login.

- ✧ Check device you want to delete, click Delete to batch delete them. Click  of device to delete one by one.
- ✧ Check device you want to export and click Export.
- ✧ When show device code is selected in system setup, device is shown with . You can click it to customize device code. This is mainly used for operation via keyboard.




Figure 3-2

3.2 Manually Add

Step 1. In Devices interface, click Add, see Figure 3-3.

The image shows a 'Manually Add' dialog box with the following fields and values:

- Device Name: * |
- Method to add: IP/Domain
- IP/Domain Name: *
- Port: * 37777
- Group Name: Default Group
- User Name: *
- Password:

Buttons at the bottom: Save and Continue, Add, Cancel.

Figure 3-3

Step 2. Set device parameter, see the following chart.

Item	Function
Device name	Please input a device name here.
Method to add	By IP/domain and SN.
IP/Domain name	Device IP address or domain name. Note: You can add device of IPV6 address.
SN	Device SN. Note: For P2P device only.
Port	Device IP port. It is 37777 by default.
Group Name	You can choose one group.
User name	The user name you login the device.
Password	The password you login the device.

Step 3. Click Add, complete adding of device. Click Save and Continue to add more devices.

3.3 Batch Import and Add Device

Before you batch import device, you shall get device info. You can export device info to get device info file.

Step 1. In Devices, click Import. See Figure 3-4.




Figure 3-4

Step 2. According to actual condition, select import method.

- Select Local tab to select device info locally.
- Select From www.easy4ip.com, enter username and password.

Step 3. Click Import. When successfully imported device, system shows a message, click OK.

3.4 Modify IP

Step 1. In Devices interface, click Search.

Step 2. Set device segment and click Search. See Figure 3-5.




Figure 3-5

Step 3. Check device you want to modify IP, click Modify IP.

Step 4. Enter username and password. Click OK.

- When you check a single device, system pops up Modify IP box, see Figure 3-6.




Figure 3-6

- When select more than one device, system pops up Batch Modify IP box, see Figure 3-7.




Figure 3-7

Step 5. Set device new IP start IP, subnet mask and gateway.

Step 6. Click Save.

4. Preview

4.1 Live view

You can live view video, local record, snapshot, enable audio, talk, instant playback, zoom in video, switch stream, config device parameter, config intelligent channel, config master-slave track, update channel info and etc.

In New tab, click Live View, see Figure 4-1.




















Figure 4-1











No	Task	Note
1	Device list	<p>You can switch streams, create device groups, create new maps, update channel information, modify channel names, log off, and log in to devices.</p> <ul style="list-style-type: none">● When the Default Device Tree is set to Device Tree (by device), the device tree displays the grouping and channels for the device.● When the Default Device Tree is set to Area Tree (by channel), the device tree displays the zones and channels.

No	Task	Note
.	Switch stream	<ul style="list-style-type: none"> ● Right-click the group / device or area, and select the main stream or sub stream. The video window will display the preview interface of all channels in the group / device or area in the main stream or auxiliary stream. <p>Note: When the number of video windows is less than the number of channels on the device, the video window displays the preview interface for all channels in a split screen.</p> <ul style="list-style-type: none"> ● Right-click the channel, select the main stream or sub stream, the video window will be the main stream or sub stream shows the preview interface of the channel. ● Select the video window in which the preview is enabled, right-click to select Stream Type> Main Stream, Stream Type> Sub Stream 1 or Stream Type> Sub Stream 2. <p>Note: You can preview both the main stream and secondary streams simultaneously on the same channel.</p>
	New device group	<p>When the Default Device Tree is set to Device Tree (by device), right-click the group in the Organizational Tree, select New Group, set the group name in the New Group box, Click Save to create a device grouping.</p> <p>Note:</p> <ul style="list-style-type: none"> ● If you need to continuously create multiple groups, set group name, and click 'Save and Continue. ● You can right-click the new group, to rename or delete the group. ● You can only delete groups without devices.
	New e-map	<p>When the Default Device Tree is set to Device Tree (by device), right-click the group in the Organization Tree area and select New Map to create a new E-Map.</p> <p>Once the map has been added, you can edit, rename, and delete the map or hotspot by right-clicking on the map or heat map.</p> <p>E-map can be displayed directly in the list of previewed devices, you can drag the map directly to the preview window to preview, you can save the map to view, easy to open the next time.</p> <p>For details on how to create a new map, see Ch 4.2.</p>
	Create zone	<p>When the Default Device Tree is set to Zone Tree (by channel), right-click the area in the Area Tree area, select New Zone, set the name in the New Zone dialog box, Click Save to create the area.</p> <p>Note:</p> <ul style="list-style-type: none"> ● If you need to continuously create multiple zones, set the name, click Save and Continue. ● You can right-click the new zone, to rename or delete the zone. ● You can only delete groups without devices.

No	Task	Note
	Device config	When the Default Device Tree is set to Device Tree (by device), right-click the device and choose Device Configuration from the shortcut menu. The Device Configuration page appears. For details about how to configure a device, see section Ch 10. The parameters of different devices may be different. For the configuration of the parameters, refer to the corresponding device manual.
	Zero Channel Preview	When the Default Device Tree is set to Device Tree (by device), right-click the NVR device and select Zero Channel Preview.
	Channel display	When the Default Device Tree is set to Device Tree (by device), right-click the storage device and choose Channel Display> Show Binding Channels or Show All Channels to switch the channel display mode.
	Modify channel name	When the Default Device Tree is set to Device Tree (by device), right-click the device channel under the storage device and select Modify Channel Name.
	IVS channel config	When the Default Device Tree is set to Device Tree (by device), right-click the device and choose IVS Channel Cfg to jump to the IVS Channel Cfg interface. See Ch 4.4.
	Alarm output	When the Default Device Tree is set to Device Tree (by device), right-click the device and select Alarm Output to turn on or off the alarm output channel.
	Configure the smart track	Right-click the device, select Smart track configuration, jump to smart track configuration interface. See Ch 4.4.
	Configure the master-slave track	Right-click the device and select Master-slave Track Configuration jump to Master-slave Track Configuration interface. See Ch 4.5.
	Update channel information / name	<ul style="list-style-type: none"> When the Default Device Tree is set to Device Tree (by device), right-click the device and select Update Channel Info to update the channel name or channel number changes. When the Default Device Tree is set to Area Tree (Per Channel), right-click the device and select Update Channel Name to update the channel name.
	Logout and login	When the Default Device Tree is set to Device Tree (by device), right-click the device and select Logout. The software and device are disconnected. After logging out, right-click the device, select Login, reconnect device.
	View	When  next to View , Open the view interface. You can create view group, modify view name, move view group, delete views, and playback view record on the view interface.
	New view group	When  next to View. Open the view interface. Click New Group, set the group name in the New Group dialog box and click Save to create the view group. <ul style="list-style-type: none"> If you need to continuously create multiple groups, set group name, and click 'Save and Continue. You can right-click the new group, rename or delete the group. You can only delete groups that have no views.

No	Task	Note
	Modify view name	When  next to View. Open the view interface. Right-click the view name and select Modify View Name.
	Delete view	When  next to View. Open the view interface. Right-click the view name and select Delete This Item.
	Move view group	When  next to View. Open the view interface. Right-click the view name, select Move View Grouping and select the group you want to move to.
	Playback view record	When  next to View. Open the view interface. Right-click the view name and select Playback to enter the playback interface. See Ch 6.
	PTZ	<ul style="list-style-type: none"> For motorized zoom devices, focus, autofocus, or focus can be reset. For PTZ setting, you can simulate the mouse, open or close PTZ menu, adjust PTZ speed, direction, zoom, focus and iris. <p>Click More Features to set Preset, Tour, Horizontal Rotation, Scan, Track, and Accessibility. See Ch 4.6.</p>
2	View real-time stream info	Select a open live window, the status bar displays real-time information stream.
	Local record	Select open video window which is ON, and click  or right click to select Start Record. Note: You can modify the saved path in System Configuration> File Settings .
	Snapshot	Select open video window which is ON, and click  or right-click to select Snapshot, snapshot a single picture. Note: You can change the path where the image is saved in System Configuration> File Settings .
	Triple Snapshot	Select the preview video window, right click Triple Snapshot, the system continuously snapshot three pictures.
	Start audio	Select open video window which is ON, and click  or right-click to select Start Audio.
	Start talk	Select open video window which is ON, and click  or right-click to select Start Talk, you can talk between the client and the device.
	Turn on the remote intercom	When you preview the channel under the storage device, and the device supports remote channel intercom, select the video window with preview opened, right-click to select Turn on the remote intercom, the remote channel on the client and the storage device can be speak.

No	Task	Note
	Start instant playback	Select open video window which is ON, and click  or right-click to select Start Instant Playback .
	Zoom in	Select open video window which is ON, and click  .
	Close window	Select open video window which is ON, and click  or right click to select Close Window .
	Close all windows	Select the video window, right-click to select Close All Windows .
3	Live preview	Double-click a device in the Organization Tree or drag the device to the video window for a live preview.
	Playback	Select the preview video window, right-click Playback to enter the Playback interface. See Ch 6.
	Fisheye installation	<p>For fisheye device only.</p> <p>Select the video window with preview ON, right click on Fisheye Installation Mode and select the installation mode according to the actual installation of the device.</p> <p>Fisheye installation mode includes  (Ceiling),  (Wall mount) and  (GND).</p>
	Fisheye view mode	<p>For fisheye device only.</p> <p>Select the preview video window, right-click the Fisheye view mode, according to the actual situation to select the desired view mode.</p> <p>The view mode is different depending on the installation mode of the fisheye. See Ch 4.7.</p>
	Split screen tracking	<p>Split screen tracking includes the normal mode, 1 +3 mode and 1 +5 mode three modes.</p> <ul style="list-style-type: none"> • Normal mode: Original image. • 1 + 3 mode: the original image and 3 sub-window, the original image can be adjusted 3 sub-window position. • 1 + 5 mode: the original image and 5 sub-window, the original image can be adjusted 5 sub-window position.
Adjust	<p>It is used to adjust the preview effect of the video screen on the client and does not change the actual image parameters of the device.</p> <p>You can adjust the brightness, contrast, saturation and hue of the video screen.</p>	

No	Task	Note
.	Smart overlay	<p>Make intelligent rules or intelligent object box displayed in the video screen.</p> <p>Select the video window with the preview turned on, right-click on the Intelligent overlay> Intelligent rule or Intelligent object box.</p>
4	Save view	<ul style="list-style-type: none"> ● Click , Save the current preview video window as a view, and you can view it instantly in the Preview, Playback, Tour interface. ● After creating the round-robin schedule, click , Check the Save to Tour Plan, you can also save the view to the tour plan. <p>See Ch 5.</p>
	Tour ON	<p>After creating a tour plan, in  shown tour plan, you can select tour plan and click  to enable tour.</p> <p>See Ch 5.</p>
5	Set video scale	<p>You can set the video aspect ratio in two ways.</p> <ul style="list-style-type: none"> ● Select the video window, right-click to select Window Scale, select the video screen display ratio. ● In Select  video screen display ratio.
	Set video window display mode	<ul style="list-style-type: none"> ● Click  In the icon, the video window is set to the corresponding number of windows display mode. ● Click , In the pop-up interface customize the video window display mode. <ul style="list-style-type: none"> ■ In the standard interface split area, select the video window display mode, click  at the upper right corner of the display, The latest collection of three video window display mode is displayed in the preview interface on the toolbar. ■ In the Custom Split area, click , Custom video window display mode. ■ Click  or select the video window, right select full screen, video window full screen display.

4.2 E-Map

Via E-map you can straightly known the location of video channel or alarm channel and live preview.

4.2.1 New Map

Step 1. Right click group in Organization Tree, select New Map. See Figure 4-2.









Figure 4-2

Step 2. Set map name, select path of picture.

Step 3. Click Save. See Figure 4-3.

Note:

- Click , create new hot zone on map, see Ch 4.2.2.
- Click , modify map name or replace map.
- Click  to adjust opacity.
- At the lower right corner, you can see aerial view of map. Click , to close aerial view and click  to open aerial view.




Figure 4-3

Step 4. Drag camera to corresponding monitor position on map to adjust camera monitor range, or drag camera alarm input into map.

Step 5. Click  to save map.

Step 6. View device live preview on map.


- a) Open Live interface, in device list double click heat map or drag heat map into preview window.
- b) On map click camera or place mouse on camera for a few seconds, in the pop-up window you can view live preview.

Note:

- Click map preview window, right click and select Open All Channels, at bottom of preview window it shows live of all devices.
- Click preview window on map, right click Video Wall, and in pop-up window it shows live of all devices.

4.2.2 New Hot Zone

For hot zone, you can add corresponding picture on map.

Step 1. In e-map interface, click . See Figure 4-4.










Figure 4-4

Step 2. Set map name, select picture path.

Step 3. Click Save. See Figure 4-5.

Note:

- Click  to create new zone.
- Click  to modify heat map name or replace heat map.
- Click  to modify heat map name or replace heat map.
- Click  to adjust camera monitor range opacity.
- At the lower right corner, you can see aerial view of heat map. Click , to close aerial view and click  to open aerial view.
- At the lower left corner, click picture window to return to previous heat zone or map.




Figure 4-5


Step 4. Double click heat map, drag camera to corresponding monitor position on map to adjust camera monitor range.

Step 5. Click  to save heat map.

Step 6. View device live preview on map.

- c) Open Live interface, in device list double click heat map or drag heat map into preview window.

Note:

In heat map preview window status bar, click  to return to map preview.

- d) On map click camera or place mouse on camera for a few seconds, in the pop-up window you can view live preview.

Note:

- Click map preview window, right click and select Open All Channels, at bottom of preview window it shows live of all devices.
- Click preview window on map, right click Video Wall, and in pop-up window it shows live of all devices.

4.3 Config IVS Channel

By setting IVS channel, you can mark depth of field of IVS plan. Different cameras support different IVS plan, subject to actual interface.

Step 1. Right click device in Organization Tree in Live View interface, select IVS Channel Config. See Figure 4-6.




Figure 4-6

Step 2. Click highlighted IVS plan, and click IVS icon you need, select IVS plan.

Step 3. Click Next. See Figure 4-7.






Figure 4-7

Step 4. Mark depth of field.

- a) Click the mark area in the video window to draw the mark area, right-click to draw after drawing to complete.
At least 3 points are required to draw in the mark area.
- b) Set the length of the vertical ruler, click , draw vertical ruler in the mark area, left-click to complete the drawing.
Repeat this step to add 3 vertical rulers to the mark area.
- c) Set the length of the horizontal ruler, click , and draw a horizontal ruler in the mark area, left-click to complete the drawing.

Note:

- Select vertical or horizontal ruler, click Re-draw, re-draw the ruler, select the calibration area, click Redraw, redraw the calibration area, the vertical scale and the horizontal ruler.
- Select the vertical or horizontal ruler, click Delete, delete the ruler; Select the calibration area, click Delete, delete the calibration area, vertical ruler and horizontal ruler.

Step 5. (Optional) Measure distance vertically or horizontally.

Note:

When you need to measure, you need to follow this step.

- a) Click Apply, to save marked depth of field.
- b) Measure distance.
 - Click vertical distance, and mark vertical line in marked area, system shows drawn vertical length.
 - Click horizontal distance, and mark horizontal line in marked area, system shows drawn horizontal length.

Step 6. Click Save.

4.4 Smart Track Config (Fisheye+Dome)

Step 1. In Live View interface, right click fisheye device, select Master0slave tracking confiig, see Figure 4-8.










Figure 4-8






Step 2. Link speed dome.

- a) In Link Speed Dome area, click  next to fisheye name.
- b) In speed dome dropdown list, select speed dome, click Save. See Figure 4-9.

Note:

You can adjust speed dome iris, zoom and focus.

- Click  to enable or disable mouse stimulation, by default it is ON.
- Click  or  to zoom.
- Click  or  to focus.

- Click  or  to adjust iris.
- Click  to draw a box via mouse on the monitor video, and speed dome will rotate and focus to this scene quickly,
-  and  cannot be enabled at the same time.





Figure 4-9


Step 3. Add mark point.

- Click Add, in fisheye live preview interface shows mark box. Drag mark box to suitable position.
- By default, to enable mouse stimulation, use mouse to drag speed dome video to suitable position.
- In mark point list, click  of corresponding mark point, save.

Repeat step 1 to 2 to add at least three mark points.

Step 4. Click OK.

Step 5. View smart track.

- Right click the fisheye device, select master-slave tracking.
See Figure 4-10.
- Link mode is enabled by default, click  to correct fisheye mode and switch link mode. Enable fisheye correction, and in fisheye preview window, right click and select fisheye installation method and view mode. See Ch 4.7.
 - On the left you can set PTZ, see Ch 4.6.




Figure 4-10

- b) In fisheye device preview interface click any spot, speed dome on the right auto links to the corresponding position.

4.5 Smart Track Config (Dome+Fixed)

After you have configured dome and fixed camera linkage, when intelligent rule of fixed camera triggers alarm, speed dome auto links to corresponding position and tracks object until the object exceeds monitor range or tracking time limit.

Condition

Fixed camera has set trip wire, zone, loitering or fast move intelligent rule.

Steps

Step 1. In Organization Tree of preview interface, right click fixed camera, select Master-slave tracking config, see Figure 4-11.




Figure 4-11

Step 2. Link speed dome.











- a) In Link Speed Dome area, right click host name.
- b) In dropdown list, select speed dome.
- c) Config track parameter, see

Parameter	Note
Expected zoom	Zoon ratio when link to speed dome tracking
Horizontal zoom angle	Horizontal zoom ratio when link to speed dome tracking
Vertical zoom angle	Vertical zoom ratio when link to speed dome tracking
Track length	Time length of speed dome
Idle length	Check Enable, to enable idle length, when speed dome no tracking time exceed set idle time, speed dome will rotate to corresponding position as set.

- d) Click Save. See Figure 4-12.

Note:

You can adjust speed dome iris size, zoom and focus.

- Click , enable to disable mouse stimulation, by default is in enabled.
- Click  or  to zoom.
- Click  or  to focus.
- Click  or  to adjust iris.
- Click  to draw a box via mouse in monitor video, speed dome will quickly position to it.
-  and  cannot be enabled at the same time.





Figure 4-12

Step 3. Add mark point.

Step 4. Add mark point.

- a) Click Add, in fixed camera live preview interface shows mark box. Drag mark box to suitable position.
- b) Be default, to enable mouse stimulation, use mouse to drag speed dome video to suitable position.
- c) In mark point list, click  of corresponding mark point, save.

Note:

Click Clear to delete all mark points.

Repeat step1 to 3 to add at least four mark points.

- d) (Optional) you can select preset in Preset.
When speed dome tracking time exceed set idle time, speed dome will rotate to corresponding position.


Note:

When idle length is enabled, need to run this step.

Step 5. Click OK.

Step 6. View smart track.

- a) Right click the fixed camera device, select master-slave tracking.
See Figure 4-13.

- Link mode is enabled by default, click  to disable auto tracking.
- On the left you can set PTZ, see Ch 4.6.




Figure 4-13

- b) When fixed camera preview interface intelligent rule triggers alarm, speed dome on the right auto link to corresponding position and track object until the object exceeds monitor range or exceed tracking length.

4.6 PTZ

Different device PTZ have different setup interface, subject to actual condition.
See the following figures and charts.




Figure 4-14




Figure 4-15

Parameter	Note
Zoom	Click or to adjust zoom.
Switch to PTZ	Click Switch to PTZ, system jumps to PTZ control.
Focus	Click or to adjust definition.
Auto Focus	Click Auto Focus to auto focus.
Reset Focus	Click Reset Focus to reset.















Figure 4-16


Parameter	Note
Menu	Click  go to PTZ menu.
Mouse stimulation	Click  , via mouse operate PTZ.
Direction	Set PTZ direction in 8 directions.
3D position	Click  , and draw a box in video monitoring, PTZ will rotate and focus to this scene.
Step	Control PTZ rotation speed, can be set 1 to 8 different rotation step.
Zoom	Click  or  to adjust zoom.
Focus	Click  or  to adjust definition.
Iris	Click  or  to adjust brightness.
Preset	By setting the Preset, you can quickly go to the preset position corresponding to the camera. Preset setting For details, see Ch 4.6.1. Note: You can set up to 128 presets.
Tour	By setting Cruise, the camera can cruise between different preset points. Cruise setting details, see Ch 4.6.2 . Note: You can set up to eight cruise group.

Parameter	Note
Horizontal rotation	By setting Horizontal rotation, the camera can be rotated horizontally. in  , Select Horizontal rotation and click  , turn on horizontal rotation.
Scan	By setting the two borders, the camera rotates repeatedly between the two borders. Scan settings For details, see Ch 4.6.3.
Pattern	By setting the Tour track, the user operation during the rotation of the camera recorded, the camera can be rotated according to the track record. Patrol track setting details, see Ch 4.6.4.
AUX	With aux, aux commands can be entered to turn on the aux points.

4.6.1 Preset

By setting the preset point, you can quickly go to the preset position corresponding to the camera.
Step 1. Via PTZ direction control the camera to designated position.

Step 2. In  select preset, click .

Step 3. In  select preset no., enter preset name.

Step 4. Click  to save preset.

Step 5. Click  to delete non-necessary preset.



Step 6. Select preset and click , camera rotates to corresponding position.

4.6.2 Tour

By setting the tour, the camera can tour between the different preset points.

Warning:

Set at least two presets before you can tour.

Step 1. In , select tour, and click . See Figure 4-17.





Figure 4-17

Step 2. Set tour no. and tour name.

Step 3. Select preset.

- a) In Preset list select preset, and enter time.
- b) Click  to add preset.

Repeat this step to add more presets.

Step 4. Click OK.


Step 5. You need to select tour no., click  so camera will tour among different presets.


4.6.3 Scan

By setting the two borders, the camera rotates repeatedly between the two borders.

Step 1. In  select Scan.

Step 2. By control PTZ direction, rotate PTZ to designated left position, click  to set left border.


Step 3. By control PTZ direction, rotate PTZ to designated right position, click  to set right border.

Step 4. Click  to repeat rotation among two borders.

4.6.4 Pattern

Record down camera rotation process, via pattern rotation function.

Step 1. In  select Pattern.








Step 2. Click  to start to set pattern, and zoom, focus or rotate camera.






Step 3. Click  to complete.

Step 4. Select pattern no., click , camera rotate pattern according to record.

4.7 Fisheye View Mode

Only fisheye device supports installation and view mode, different installation modes corresponding to view mode referring to the following chart.

parameter	Description	
View mode	<p>Current video screen (by default support the original image mode), in accordance with the different installation methods, with other different presentation as follows:</p> <ul style="list-style-type: none"> • Ceiling: 1P + 1, 2P, 1 +2, 1 +3, 1 +4, 1P +6, 1 +8. • Wall mount: 1P, 1P + 3, 1P + 4, 1P + 8. • GND: 1P +1,2 P, 1 +3, 1 +4, 1P +6, 1 +8. <p>Note: When switching installation mode, by default show the original image mode.</p>	
Ceiling/wall mount/GND	 original image	That is the original image has not been corrected.
Ceiling	 1 + 2	That is the original image plus two independent videos and the original image sub-frame support zoom, move.
Ceiling / wall mount	 1P + 1	Expand the rectangle that is 360 ° panoramic + independent sprite and rectangular expansion panorama sub image support zoom, move operation, expand the rectangle starting about Panorama also supports the move operation.
	 2P	That is 180 ° rectangular two associated expanded screen, any time two sub-windows are composed of 360 ° panorama, also known as double Panorama, two rectangular stretches the picture support and move around the starting point of the operation, and mutual interaction.
	 1 + 3	That is the original image +3 independent videos and the original image sub-frame support zoom, move.
	 1 + 4	That is the original image +4 independent videos and the original image sub-frame support zoom, move operation, the original image also supports changing the rotation starting operation.
	 1P + 6	This is rectangle that is 360 ° panoramic +6 independent videos and rectangular expansion panorama sub frame support zoom, move operation, expand the rectangle starting

		about Panorama also supports the move operation.
	 1 + 8	That is the original image +8 independent videos and the original image sub-frame support zoom, move.
Wall mount	 1P	That rectangle from left to right 360 ° panorama unfold, 180 ° panoramic rectangular expand operations to support moves up and down to change the vertical viewing angle.
	 1P + 3	Expand the rectangle that is 360 ° panoramic +3 independent videos and rectangular expansion panorama sub frame support zoom, move operation, rectangular panoramic expand support moves up and down operation, change the vertical viewing angle.
	 1P + 4	Expand the rectangle that is 360 ° panoramic +4 independent video and rectangular expansion panorama sub frame support zoom, move operation, rectangular panoramic expand support moves up and down operation, change the vertical viewing angle.
	 1P + 8	Expand the rectangle that is 360 ° panoramic +8 independent videos and rectangular expansion panorama sub frame support zoom, move operation, rectangular panoramic expand support moves up and down operation, change the vertical viewing angle.

5. Tour & Task

By setting tour plan, you can tour each window.

Step 1. In New function tab, click Tour & Task.

Step 2. Add tour plan.

- a) Click Add. See Figure 5-1.





Figure 5-1

- b) Double click tour plan name or click  to modify tour plan name.

Step 3. Set task.

- a) Click . See Figure 5-2.





Figure 5-2

- b) Set task name and time span, according to actual condition click  to set four window number.
- c) Double-click the channel of the device or drag the channel of the device into the video window in the order that you want. See Figure 5-3.

Note:

- In the Organization Tree, right-click a storage device, select the Bind all channels, the storage channel in turn is bound to the corresponding video window ; select the video window to be bound in the Organization Tree, right-click a storage device, select the tie given zero channels zero bound channel to the selected video window.
- Select the video window to be bound, under the Organization Tree, right-click the channel storage devices, select the Bind channel, the channel will be bound to the selected video window.
- Select Bind video window, right-click the organizational tree in the front-end device, select the Bind IPC, the front-end device bind to the selected video window.
- After the video channel bonding, right-click the video window, remove binds or remove all binds.








Figure 5-3

d) Set channel preset, time span, stream type and channel sequence.

Note:

- Click  of the corresponding channel, in the left preview screen to display live preview or e-map information.
- Click  or  of the corresponding channel, adjust the channel sequence in the task.
- Click  of the corresponding channel, delete the corresponding channel.

e) Click Save, See Figure 5-4.





Figure 5-4

Step 4. Enable tour task.

- a) In New function tab, click Preview.
- b) Click tour plan below.
- c) Click  to run the plan.

6. Playback

6.1 Playback

You can playback and export device record, device picture, local record and local picture.

In New tab, select Playback, see Figure 6-1.

























Figure 6-1

No.	Task	Note
1	Playback video	You can play back the recording device. For details, see Ch 6.2.
	Playback image	You can picture playback device. For details, see Ch 6.4.
	Playback local video	You can play back the local video. For details, see For details, see Ch 6.6.
	Playback local picture	You can play back the local picture. For details, see For details, see Ch 6.8.
	Organization Tree / Area Tree	<ul style="list-style-type: none"> When the Default Device Tree is set to Device Tree (by device), the device tree displays the grouping and channels for the device. When a default device tree is set to Area Tree (by channel), the device tree display channel.

		Default Device Tree setting, see Ch 8.
	Logout and login	When the Default Device Tree is set to Device Tree (by device), right-click the device and select Logout. The software and device are disconnected. After logging out, right-click the device, select Login, reconnect device.
	View	In the Device tab, click  behind View . Open View interface, playback view video device. For details, refer to Ch 4.1.
2	View playback stream information	Choose video window with open video, in status bar it displays the playback stream information.
	Snapshot	Select open video window, click  or right-click to select Snapshot, Snapshot a single picture. You can click  in the homepage, modify the path to save the picture.
	Zoom	Select open playback video window, click  .
	Close window	Select Open playback video window, click  or right click to select Close Window .
	Close all windows	Select the video window, right-click to select Close all windows .
3	Set aspect ratio	Select the video window, right-select Window Scale, select the video aspect ratio.
	Enable Audio	You can turn on the audio through the following two ways. <ul style="list-style-type: none"> ● Select open playback video window, right-select Audio. ● Playback control toolbar at the click , and adjust the volume.
4	Set the device record search criteria	In the Devices tab, select the device or view, select Record, set the record type, stream, start time and end time, click Search, the recording information is displayed in the schedule box. <ul style="list-style-type: none"> ● Record type includes all types of video record, general record, alarm record, motion detection record, intelligent record and card record. ● Stream includes main stream and sub stream. ● Interval of start time and end time must be within a day.
	Set the device picture search criteria	In the Devices tab, select the device, or view, select Picture, set the start time and end time, click Search, image information is displayed in the playback window. Interval of start time and end time must be within a day.
5	Time	Show existing video display information.

	progress bar	
6	View progress bar	Click  to view the video or image export progress and export results.
	Export record	Export device video files, see Ch 6.3.
	Export picture	Export device picture files, see Ch 6.5.
	Export local record	Export local video files. See Ch 6.7.
	Open Video	In the Local>
	Smart search	Select open playback video window, click  , in the video playback window, select the smart search, click device  again. The software will search for the video motion detection, click  to exit the smart search.
7	Playback control toolbar	<p>Control video playback and audio.</p> <ul style="list-style-type: none"> ●  Video playback from the same point in time for all channels. ●  Reverse video playback. ●  Start video playback. ●  Pause video playback. ●  Stop video playback. ●  Single frame backward playback. ●  Single-frame forward playback. ●  Adjust the playback speed.
8	Set the video window display mode	<ul style="list-style-type: none"> ● In  select the desired video window display mode or select  to customize video window display mode. ● Click  or select the video window, right select full screen, video window full screen display.
9	Video file list	Click the icon to expand the list of the corresponding channel video file, you can select video files for playback and export the corresponding video file.

6.2 Playback Device Record

Condition

There is device record inside channel.

Steps:

Step 1. In playback interface, click Device tab.

Step 2. In Organization Tree, select device channel or select view in View.

Step 3. Select record and set record search criteria.

- a) Select record type and stream, and set time.
- b) Click Search.

Step 4. Select window with record, click .

See Figure 6-2.




Figure 6-2

6.3 Export Device Record

Condition

There is device record inside channel.


Steps:



Step 1. In playback interface, click Device tab.

Step 2. In Organization Tree, select device channel or select view in View.

Step 3. Set record search criteria.

- a) Select record type and stream, and set time.
- b) Click Search.

Step 4. Select window with record, click .

Step 5. Click , system select one record, and adjust record part according to actual need, click  again to export record. See Figure 6-3.




Figure 6-3

Step 6. Select export path and format.

Note:

When the Export Format is set to Original Format, please also check the Export Smart Player, export original format player.

Step 7. Click OK.

The system displays the playback stop information, click OK.

The system displays the Export Progress dialog box, as Figure 6-4 below.

After recording the download is complete, the system prompts the download is complete.

Click Exporting tab, you can view the video download progress, pause the video being exported to continue downloading paused video, download it again failed to download videos and delete are exporting video; click exported tab, you can view download history and open video storage path.




Figure 6-4

6.4 Playback Device Picture

Condition


There is device picture inside channel.



Steps

Step 1. In Playback interface, select Device tab.

Step 2. In Organization Tree, select device channel or in View select view.

Step 3. Select picture and set time. See Figure 6-5.

Click  on the right, you can open and close device picture list.

In device picture list, click , device picture list will be shown in format of list; click , device picture list is shown in format of thumbnail.





Figure 6-5

Step 4. Playback picture.


- Manual playback: Click Next or Preview.
- Auto playback: Slide  to auto play, and set interval, system will auto playback local picture.

6.5 Export Device Picture

Step 1. In Playback interface, select Device tab.

Step 2. In Organization Tree select device channel or in View select view.

Step 3. Select Picture and set time.

Step 4. Click  on the right, to export device picture.

Step 5. Click . See Figure 6-6.




Figure 6-6

Step 6. Select export path, click OK. See Figure 6-7.

Click Exported tab, you can view download record, open picture storage path and delete downloaded file.




Figure 6-7

6.6 PlaybackLocalRecord

Condition



There is local record in the channel, see Ch 4.1.


Steps

Step 1. In Playback interface, select Local tab.

Step 2. Click Record tab.


System shows local record list.

In local record list, click , display in list mode. Click , display in thumbnail mode.

Step 3. Select record to playback, click  or double click record.

See Figure 6-8.

Note:

You can click  to open local record file for playback.




Figure 6-8

6.7 Export Local Record

You can export local record.


Condition

There is local record in this channel, see Ch 4.1.

Steps

Step 1. In Playback interface, click Local tab.

Step 2. Click Record tab.

Step 3. Check record to export, click . See Figure 6-9.




Figure 6-9

Step 4. Select export path and format.

Note:

When Export Format is set to Original Format, please check Export Smart Player to export.

Step 5. Click OK.

The system displays the Export Progress dialog box, as Figure 6-10 shown.

After record download is complete, the system prompts the download is complete.

Click Exporting tab, you can view the video download progress, pause the exported video, resume download paused, and delete videos are exporting video; click Exported tab, you can view the download history, open video storage path and delete the downloaded file.




Figure 6-10

6.8 Playback Local Picture

Condition



There is local picture in the channel, see Ch 4.1.


Steps

Step 1. In Playback interface, select Local tab.

Step 2. Click Picture tab.

System shows local record list.

In local picture list, click , display in list mode. Click , display in thumbnail mode.

Step 3. Select picture to playback, click  or double click picture
See Figure 6-11.





Figure 6-11


Step 4. Playback picture.

- Manual playback: Click Next or Preview.
- Auto playback: Slide  to auto play, and set interval, system will auto playback local picture.

7. Log Search

7.1 Search Client Log

Step 1. In New tab, click Log.

Step 2. Select . System shows Client interface.

Step 3. Set time, type, keyword. Client log includes system log, operation log and alarm log.

Step 4. Click Search. See Figure 7-1.

Note:

After log is successfully searched, you can click Export to export log.




Figure 7-1

7.2 Search Device Log

Step 1. In New tab, click Log.

Step 2. Select .

Step 3. Set time, type, and device. Client log includes system log, config log, storage log and etc.

Step 4. Click Search. See Figure 7-2.

Note:

After log is successfully searched, you can click Export to export log.

SMART PSS Log + 16:44:04

Time: 2016/10/25 00:00:00
2016/10/25 23:59:59

Type: All Type

Device: 1

[Search](#) [Export](#)

No.	Time	User Name	Log Type	Note
1	2016-10-25 16:24:34	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
2	2016-10-25 16:24:37	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
3	2016-10-25 16:24:38	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
4	2016-10-25 16:24:38	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
5	2016-10-25 16:24:39	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
6	2016-10-25 16:24:40	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
7	2016-10-25 16:25:08	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
8	2016-10-25 16:25:19	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
9	2016-10-25 16:26:00	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
10	2016-10-25 16:26:13	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
11	2016-10-25 16:26:15	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
12	2016-10-25 16:26:16	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
13	2016-10-25 16:27:46	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
14	2016-10-25 16:27:47	System	Event Begin	Channel NO. : 1, Event Type : Motion Detection, Region Name
15	2016-10-25 16:27:47	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name
16	2016-10-25 16:27:47	System	Event End	Channel NO. : 1, Event Type : Motion Detection, Region Name

Every page shows 100

K < 1/5 > | Jump to page Jump

Figure 7-2

8. System Config

You can set up base info, preview, event, log, system and language, hot keys, and file path, backup of system.

Step 1. In homepage, click . See Figure 8-1.




Figure 8-1

Step 2. Set parameters, see the following chart.

Parameter Type	Parameter	Note
Base	Initial page	Select page shown when you open the software, including new feature page preview interface and will recovery not closed tabs
	Maximum behaviour	Maximize display software, including full screen and maximized window.
	Minimum behaviour	Check show floating window, display floating window when the software is minimized.
	Default video scale	Set the preview or playback video default ratio, including the original scale and full screen.

	Default device tree	<p>Set the preview, playback and other interface devices tree display formats. Modify this parameter to take effect after the restart the software needed.</p> <p>Include following options:</p> <ul style="list-style-type: none"> ● Device tree (according to device): grouping by device ● Area tree (according to channel): grouping by channel
Live View	Instantly Replay Time	Set at time instant replay of the preview screen.
	Resume last preview	Check the Resume last preview software record video window status when closing software, and after re-login open the preview screen, the video will be restored as before the software is closed.
Playback	Save device tree selection	Enable the Save Device Tree check box. After the video search is finished, the device remains selected.
Device	Show device channel number	Check the Show device channel number, then in Device interface software automatically assigns a unique no. to device, you can modify this no. This no.of device is used for keyboard.
	Auto login device	Check the Auto login device, restart the software, the software automatically logged added device. Modify this parameter to take effect after the restart the software as needed.
	Auto fill user and key	<p>Check the Auto fill user and key, enter your username and password, the software automatically login added device according to the username and password.</p> <p>If the login username and password set are the same as user and password of the device, then login is successful, otherwise the login fails.</p>
event	Loop	Check the Loop, looping alarm when an event occurs.
	Global wav	<ul style="list-style-type: none"> ● Check the Global wav, select audio file path, then all alarms shall play the audio file. ● Not check the Global wav, select different types of events and events in the drop-down list, and separately set their corresponding audio file.
Log	Log saved time	Setting the log storage time, modification to this parameter will be effective only after this software is restarted.
System and	Network ability	Set the network according to actual network performance.

language	Auto check time	Check the Auto check time, and set the corresponding point in time, when the software is open during sync time, and the software automatically synchronize with your local PC time.
	Check time	Click Check time, the software immediately synchronization time.
	Language	Set the language of the software, modify this parameter to take effect after the restart the software as needed.
Hotkeys		<p>Set shortcut keys for common operations systems. Double click the column in the corresponding function of the hotkey, then set the hotkey function on the keyboard, click the Apply, modify the corresponding hotkey function.</p> <p>Click Reset to restore default software.</p> <p>Common operations include preview full-screen playback, playback module open, open the event module, open the System Configuration, open polling configuration program, open /close the round robin program, snapshot, lock, switch users to open / close linkage video, turn on / off video .</p>
File path	Pic path	Set picture path.
	Record path	Ser record path.
Backup and Restore	Backup	Click Backup to export the software configuration file.
	Restore	Click Restore, select the previously exported software configuration file, the software reverts to the time saved configuration.

Step 3. Click Save.

9. User

9.1 Role Info

You can add, modify and delete role.

Step 1. In New tab, click User, see Figure 9-1.





Figure 9-1

Step 2. Click . See Figure 9-2.




Figure 9-2

Step 3. Set role name and fill in remark.

Step 4. Check menu right of the role, and select tab and set role channel right in Channel right area.

Note:

When user of the corresponding role logs in client, and in New tab it does not show non-allocated menu right, and in corresponding device tree it does not show non-allocated channel right.

Step 5. Click Save.

Note:

Admin has all rights which cannot be modified or deleted. After a role is added, you can modify its right or delete it.

Warning:

When you delete a role, users of this role will also be deleted.

9.2 User

You can add, modify and delete user.

Step 1. In New tab, click User. See Figure 9-3.




Figure 9-3

Step 2. Select role which you want to add user. See Figure 9-4.




Figure 9-4

Step 3. Set user parameter, see the following chart.

Parameter	Note
Username	Username which cannot repeat existing username.
Role	Select a role the user belongs. Different user permissions are for different roles.
Password	The user's password and confirm the password.
Confirm	
Remark	Description of the user information.
Menu rights	According to the actual need select the user's menu rights
Channel rights	According to the actual need select the user's channel rights

Step 4. Click Save.

Note:

Admin has all rights which cannot be modified or deleted. After a role is added, you can modify its right or delete it.

10. Device Config

You can update software, connect to WEB, configure device camera, network, PTZ, event, storage, system and etc.

In New tab, click Device CFG, see Figure 10-1. Different devices may have different parameters, subject to actual device and manual.




Figure 10-1

No.	Task	Note
1	Device	Select device, you can view the device's IP address, device model, software version and serial number.
	Upgrade	Select device, click the Upgrade, you can upgrade the device software.
	Link to WEB	Select the device, click the Link to WEB, can be linked to WEB login screen device.
2	Camera	<p>Select device, open the Camera .</p> <ul style="list-style-type: none"> ● Click Remote Device, you can search device and add the device or remove device. ● Click the Camera, you can configure the camera attributes, operations, management or head profile. ● Click the Video, you can configure the video stream, or snapshot stream video overlay information. ● Click the Audio, you can configure the audio code stream, input type and volume.

	Network	<p>Select the device, open the Network tab.</p> <ul style="list-style-type: none"> ● Click TCP / IP, you can configure a static IP address of the device or the device to obtain an IP address via DHCP. ● Click Connect, you can configure the maximum number of connected devices and the port number to use when connecting. ● Click PPPOE, you can configure the PPPoE username and password to access the device via PPPoE dialing. ● Click DDNS, you can configure the device and DDNS server domain names, access device through its domain name. ● Click the IP Rights, you can configure a whitelist and blacklist devices. ● Click SMTP (e-mail), you can configure the device's SMTP server and mailbox information when the device is configured alarm linkage and alarm messages, the recipients of the message recipient to send alarm information. ● Click FTP, the device can be configured FTP upload information and pictures, pictures in the manner set upload FTP appropriate directory. ● Click Multicast, you can configure the multicast address and port, through surveillance video multicasts. ● Click Alarm Center, you can configure the alarm center host IP address and timing login time.
	PTZ	<p>Select device, open PTZ tab. Click PTZ, you can configure PTZ and stimulate PTZ.</p>
	Configuring event parameters	<p>Select the device, open Events tab.</p> <ul style="list-style-type: none"> ● Click the Video Detect, you can configure motion detection, video loss detection, video tampering detection and defocus detection. ● Click the Audio Detect, you can configure audio input and sound intensity abnormality. ● Click Intelligent Analysis, can mark video quality diagnosis, general behavioral analysis, face detection, people counting and depth of field heat map. ● Click Alarm I/O, you can configure the alarm inputs and alarm linkage information. ● Click Abnormality, you can configure no space, storage device error, IP conflict and etc.
	Storage	<p>Select device, open Storage.</p> <ul style="list-style-type: none"> ● Click Schedule, you can configure the video snapshot and snapshot plan. ● Click HDD Manager, you can configure and view locally stored information about the device, configure the FTP server. ● Click the Record, you can configure the video stream control method.
	System	<p>Select the device, open the System tab.</p>

	Parameters	<ul style="list-style-type: none">• Click General, you can basic information and time.• Click PTZ, you can configure the analog PTZ information.• Click Account, you can add, delete users and user groups.• Click Maintenance, you can configure serial information, system configuration and maintenance information plus view version information.
--	------------	--

11. Event Config

11.1 Event Type

In New tab, click Event Config, see Figure 11-1.

Note:

Client shows all event types, different devices support different event types, subject to actual device.




Figure 11-1

The event type	Event	Note	Condition
Channel event	Video loss	Network abnormality causing video loss	Video loss detection is ON.
	Video tampering	Event is generated when video is tampered.	Video tampering is ON.
	Motion detect	Event is generated when it is detected moving object in video.	Motion detect is ON.

	Audio abnormal	Event is generated when the audio connection is abnormal.	Audio abnormal is ON. .
	Audio mutation	Event is generated when the sound suddenly changed.	Audio mutation is ON.
	Defocus detect	Event is generated when defocus occurs.	Defocus detect is ON.
IVS Alarm	Tripwire	Event is generated when the target cross line from set direction.	Tripwire is ON.
	Intrusion	Event is generated when the object enters or leaves the area, or the target appears in the region.	Intrusion is ON.
	Scene switch	Event is generated when the scene changes.	Scene switch is ON.
	Abandoned object detection	Event is generated when the monitor screen have left more than the target time set by the user.	Items turned legacy detection.
	Missing object detection	Event is generated when the monitor screen after the target is removed over a certain time.	Items move detection is turned on.
	Face detection	Event is generated when the monitor screen detects the person's face.	Face detection is ON.
External event	Alarm input 1 to input n N are different according to device alarm input structure.	Event is generated when there is external alarm input.	Device has alarm input interface.

Device Event	No disks	Event is generated when the device does not have storage devices.	No disks is ON (SD card or hard disk).
	Disk fault	Event is generated when the device has hard disk failures.	Disk fault is ON.
	Disk full	Event is generated when the device disk is full.	Disk full is ON.
	Illegal access	When the login password you enter are consecutively incorrect, and reach the limit, event is triggered.	Illegal access is ON.


11.2 Event Alarm Link Config

11.2.1 Link Notice

After set link notice, when event occurs, it will alarm or alarm flash on map.

Step 1. In New tab, click Event CFG.

Step 2. Click device and select event type.

Step 3. Slide  to turn on event, click Notify tab. See Figure 11-2.




Figure 11-2

Step 4. According to need, slide  to enable alarm sound or map flash.

Step 5. Click Save.


Click Copy to, you can link config of this camera to other device.

11.2.2 Link Video

After you link video, when corresponding event occurs, it will link corresponding camera preview or record.

Step 1. In New tab, click Event CFG.

Step 2. Click device and select event type.

Step 3. Slide , to enable event, and click Video tab. See Figure 11-3.




Figure 11-3


Step 4. Select video window, and double click camera you want to link, directly drag it into window.

Note:

On , you can set display mode.

Step 5. In camera list to be linked, set camera preset, link record or preview stream type, whether auto open video and enable record when event occurs, linked record or preview duration.

Note:

Click , you can delete camera.

Step 6. Click Save.


Click Copy to, you can copy camera link config to other devices.

11.2.3 Link Alarm Output

After you config link alarm output, when alarm occurs, it will link corresponding camera alarm output.

Step 1. In New tab, click Event CFG.

Step 2. Click device and select event type.

Step 3. Slide  to enable event, and click Alarm Out tab. See Figure 11-4.




Figure 11-4

Step 4. Select alarm output of link camera and set whether to auto enable and duration.

Step 5. Click Save.


Click Copy to, you can copy camera link config to other devices.

11.2.4 Arm Time

Event is armed all-day by default. You can set arm time as needed.

Step 1. In New tab, click Event CFG.

Step 2. Click device and select event type.

Step 3. Slide  to enable event and click Arm Time tab. See Figure 11-5.,





Figure 11-5

Step 4. In corresponding day of week drag mouse to delete to add arm time. You also can click


 of each day of week to set arm time in pop-up box.

Step 5. Click Save.

Click Copy to, you can copy camera arm time config to other devices.

11.3 Event View

You can view the alarm event information, disable event sounds or disable alarm linkage pop video, pause refresh of event information.

In homepage, click  or in New tab, select the Event, see Figure 11-6.

- In the Event interface you can view real-time alarm information, view up to 1000 latest messages, please search historical alarm message in log, see Ch 7.
- Select event, you can check Disable sound to disable the alarm sound for event; check Stop link video popup to prohibit pop-up video; check Stop refresh to pause refresh of event.
- Select event, click the Confirm, you can add a description to the event.
- After you handle event or confirm event, you cannot change the status of the event.




Figure 11-6

12. Video Wall

12.1 Video Wall

You can set video wall layout, live preview on wall, scheme and tour plus playback on wall.

In New tab, click Video Wall, see Figure 12-1.




















Figure 12-1

Serial number	Task	Note
1	Device list	<ul style="list-style-type: none"> When set Default Device Tree to Device Tree (by device), the device tree displays device group and channels for the device. When set Default Device Tree to Area Tree (by channel), the device tree displays device channels. <p>See Ch 8.</p>
	Preview	<ul style="list-style-type: none"> Right click device channel and select Preview, display corresponding device channel in the Preview area. Select video wall with bound device channel, in Window Details area>Operation column, click , corresponding video will be displayed in the video preview area.
	Switch stream	<p>You can switch stream through the following two ways.</p> <ul style="list-style-type: none"> Right click device channel and select stream type, and set the desired stream.

		<ul style="list-style-type: none"> Select video wall with bound device channel, right click to select stream type, and set the desired stream.
	PTZ	<p>There are two ways you can enter PTZ control interface.</p> <ul style="list-style-type: none"> Click PTZ area, the system displays the PTZ control interface. Select video wall with bound device channel, select the right to switch to the head, the system pop-up PTZ control interface. <p>See Ch 4.6.</p>
2	Video wall	<p>Set video wall layout and channel video preview on the wall.</p> <p>See Ch 12.2.</p>
	Scheme tour	<p>Add scheme, set tour and enable tour.</p> <p>See Ch 12.3.</p>
3	Clear video source	<p>Select screen with bound device channel, right click to select Clear Video Source.</p>
	Bottom	<p>Select screen with bound device channel, right click to select Bottom, to set the video wall to the bottom.</p>
	Set wall mode	<p>Select screen with bound device channel, right click to select Wall mode>Live or playback on wall, set video wall mode.</p>
	Open Audio	<p>Select screen with bound device channel, click  at the upper right corner of the screen, to turn on audio.</p>
	Paste	<p>Click  the window will occupy the physical screen of the window.</p>
	Maximize	<p>Click , the window will fill the window in the whole screen.</p>
	Close	<p>Click  to close the window.</p>
4	Window details	<p>In Window Details area of the screen you can view the channel information, set tour video channel time span and stream type, preview video channel, adjust order of video channels or delete unwanted video channel.</p>
5	Set video wall layout	<p>Click  to switch video wall display layout.</p>
6	Function bar	<ul style="list-style-type: none"> Click  in the pop-up screen switch box, select screen on or off screen. Click  to refresh the screen information. Choose bound NVR device or device channel video wall in

		<p>group, click  to open tour; click  to close tout.</p> <ul style="list-style-type: none"> ● Click  to delete the selected window. ● Click  to clear the screen. ● Click , you can select multiple windows, then the icon  changes to ; click a window. ● Click  to display window number and video wall number.
--	--	---

12.2 Set Video Wall and Output

Condition

Decoder and video wall are connected successfully.




Steps

Step 1. Add decoder, see Ch 3.

Step 2. Set video wall layout.

a) In video wall interface, click in pop-up box. See Figure 12-2.

Note:

Select multiple screens, click  to add splicing screen; select splicing screens, click  to cancel splicing screen; click  to clear screen config.




Figure 12-2

- b) In basic config interface, set video wall name, select Layout, and click in video wall, to add video wall layout.
- c) Click Next. See Figure 12-3.






Figure 12-3

d) Drag decoder into slot, to bind decoder and screen.

Note:


- Screen display, to show screen no., click Hide number to hide screen number.
- If you want to cancel bound decoder slot, right click corresponding screen and select Cancel Binding.

e) Check Apply Now to immediately use this config; click Finish to complete setup.

Note:



Check Apply Now, then return to video wall interface to enable this config.

Step 3. Preview channel video on wall.

a) In Video Wall interface, click layout you want, and slide , to enable video wall layout.

See Figure 12-4.

Note:

In pop up box, select video wall layout, click  to modify video wall layout, click  to delete layout. See Figure 12-4.




Figure 12-4

- b) Drag device channel into screen, bind channel and screen.
Video of corresponding channel is played in the screen, and channel info will be show in Window Details area.

Note:


- Via window split, you can enable window in screen.
- When the device supports roaming, you can drag window randomly among all screens.
- When you drag NVR to the screen, then all channels of NVR are toured on video wall. You can view tour window channel info in Window Details area. You can set tour channel time span and stream type and preview channel video in Operation column, adjust channel order or delete channel.

12.3 Scheme Tour on Video Wall

Step 1. Add scheme.

- a) Select video wall layout and bind channel.

- b) Click . See Figure 12-5.





The 'Add Plan' dialog box features a title bar with a close button (X). Below the title bar is a text input field labeled 'Plan Name:'. At the bottom of the dialog, there are two buttons: 'Save' and 'Cancel'.

Figure 12-5

- c) Set scheme name, click Save.
Repeat step a to c to add more schemes.

Step 2. Set scheme tour.

- a) Click . See Figure 12-6.



The 'Scheme Configuration' dialog box has a title bar with a close button (X). It contains a 'Dwell time (seconds):' field with the value '10' and a range '(10-120)'. To the right is a 'Select Scheme:' dropdown menu showing 'P2' and an 'Add Scheme' button. Below this is a table with two columns: 'Scheme Name' and 'Operation'. The table contains one row with 'P1' in the 'Scheme Name' column and three icons (up arrow, down arrow, trash) in the 'Operation' column. A 'Save' button is located at the bottom right of the dialog.

Scheme Name	Operation
P1	↑ ↓ 🗑️


Figure 12-6

- b) Set time span and select scheme, click Add Scheme. Repeat this step to add more schemes.

Note:

You can adjust scheme order and delete scheme in Operation column.

- c) Click Save.

Step 3. Click  to enable scheme tour.

Click  to disable scheme tour.

12.4 Playback on Video Wall

Playback device channel record on video wall.

Condition

- Complete video wall config.
- Record exists in device channel.

Steps

Step 1. Select screen with bound device channel, right click Video Wall>Playback on Video Wall.

See Figure 12-7.




Figure 12-7

Step 2. Select record type and stream type, and set time.

Step 3. Click Search.

Step 4. Select record file, click  to playback record.

13. People Count

You can search and export people count result, contrast by time and channel and export people count data.

Condition

- Enabled entrance/exit statistics function.
- Entrance/exit statistical data exists in device.

Steps

Step 1. In New tab, click People Count. See Figure 13-1.




Figure 13-1

Step 2. Select channel with people count data, and set time and period for search.

Note:

- You can search people count data by date, time, year or month.
- If you select multiple channel, then it will search data of these channels in search period

Step 3. Click Search.

The system shows people count result in this period, see Figure 13-2.





Figure 13-2

Step 4. Contrast people count results.

- a) Select statistical figure type, set filter to be ex Enter or Exit, and drag  to enable contrast.

See Figure 13-3.




Figure 13-3

- b) Set contrast type to Channel and select channel for contrast. This contrasts people count results of different channels within the same period. Set contrast type to Time and select time for contrast. This contrasts people count results of different periods for the same channel. System shows result.

14. Heat Map

You can search object moving accumulated density in device monitor image.

Condition

- Device has enabled heat map statistics.
- Heat map data exist in device.

Steps

Step 1. In New tab, click Heat Map. See Figure 14-1.




Figure 14-1

Step 2. Select camera with existing heat map data, and set search time and period.

Note:

You can search heat map data by date, period, or day of week.

Step 3. Click Search. System shows object moving accumulated density result of this period monitored by device.

Click Export to export heat map data.

15. PC-NVR

After PC-NVR is added, you can manage disk, manage channel, set record plan and view version.

Condition

- PC-NVR is installed and running now.
- See Ch 3 to add PV-NVR.

15.1 Disk Manager

Step 1. In New tab, click PC-NVR.

Step 2. Select HDD tab, see Figure 15-1.




Figure 15-1

Step 3. Select record plan when HDD is full, and set disk space, click Allocate.

System pops up info box, click OK.

Warning:

Re-allocate disk space, system will delete all record files on the disk, be careful!

15.2 Channel Management

Set channel info to pass PC-NVR record plan.

Step 1. In New tab, click PC-NVR.

Step 2. Select Channel Management tab, see Figure 15-2.








Figure 15-2

Step 3. In device list select device channel, click . System will add the selected device channel to list on the right.

Note:

- Click  to add device channel and shown in thumbnail, click  to add device channel and shown in list.
- If you delete unwanted device channel, check box in front of one device channel or check Selected channel to select all channels, click  to delete.

Step 4. Click Save.

15.3 Set Record Plan

For the selected channel, set record schedule, motion detect, alarm, MD& alarm, or smart record plan.

Step 1. In New tab, click PC-NVR.

Step 2. Select Record Plan tab. See Figure 15-3.





Figure 15-3

Step 3. Select channel to set record plan, select stream type, set pre-record time and delay record time.

Step 4. Check record type, and select record time in corresponding day of week bar.

Note:

You can click  next to each day of week bar, and in pop-up box set record type and period.

Step 5. Click Save.

Note:

- Click Copy to, and check device channel, you can copy the record plan in this channel to other device channel.
- Click Default to restore default status of device channel record plan.

15.4 Version Info

You can view PC-NVR name, storage path and version.

Step 1. In New tab, click PC-NVR.

Step 2. Select Version tab, see Figure 15-4.





Figure 15-4

15.5 Modify Port

Step 1. Click  at the lower-right corner of PC, select PC-NVR Setting. See Figure 15-5.






Figure 15-5


Step 2. Click  and enter port no. you want.

If you slide  to enable auto ON, after PC boots up, PC-NVR will be ON automatically.

Step 3. Click Save.

15.6 Modify Password

Step 1. Click  at the lower-right corner of PC, select Password Setting. See Figure 15-6.



The screenshot shows a 'Password Setting' dialog box. The 'User:' field is set to 'admin'. There are input fields for 'Original Password:', 'New Password:', and 'Confirm:'. The 'Level:' field has three radio buttons. At the bottom right, there are 'Save' and 'Cancel' buttons.

Figure 15-6

Step 2. Enter original password, and enter new password, confirm new password.

Step 3. Click Save.

Note:

- This manual is for reference only. Slight difference may be found in the user interface.
- All the designs and software here are subject to change without prior written notice.
- All trademarks and registered trademarks are the properties of their respective owners.
- If there is any uncertainty or controversy, please refer to the final explanation of us.
- Please visit our website or contact your local service engineer for more information.