

5MP HDCVI Vari-focal Dome Camera

Starlight IR Camera



HDCVI

- 1/2.8-in. 5 MP Progressive-scan STARVIS™ CMOS Sensor
- 5 MP (2592 x 1944) at 20 fps Maximum Resolution
- 2.7 mm to 13.5 mm Motorized Vari-focal Lens
- Starlight Technology for Low-light Applications
- True Wide Dynamic Range (120 dB) and 2D/3D Noise Reduction
- HD or SD Output, Switchable
- Supports Multiple Video Formats: HDCVI, CVBS, AHD and TVI
- Maximum IR Length 30 m (98 ft), Smart IR
- IP67 Ingress Protection and IK10 Vandal Resistance
- Dual Power Input, 24 VAC or 12 VDC
- Five-year Warranty*



System Overview

Experience the superior clarity of Dahua's 5 MP HDCVI cameras for vast coverage and superior image details. The 5 MP HDCVI series leverages existing coax infrastructures to deliver forensic-level images seamlessly and over long distances. The camera uses a STARVIS™ sensor and a next-generation ISP chip technology developed by Dahua to deliver stunning video. This home-grown ISP features the latest image processing algorithms and is optimized for surveillance camera operations. With total control of the ISP features and production, Dahua can offer the latest security systems at a cost-effective price.

Functions

Three Signals over One Coaxial Cable

HDCVI technology simultaneously transmits video, audio, and data over a single coaxial cable. Dual-way data transmission allows the HDCVI camera to communicate with an HCVR to send control signals or to trigger alarms.

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing details in low-light applications. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Long Distance Transmission

HDCVI technology guarantees real-time transmission over long distances without loss of video quality. HDCVI cameras provide the same resolution as most IP network camera systems using existing RG-59, RG-6, or CAT 6 UTP cabling.

Simplicity

HDCVI technology seamlessly integrates traditional analog surveillance systems with upgraded, high-quality HD video, making it the best choice to protect security investments. The plug and play approach enables full HD video surveillance without the hassles of configuring a network.

Broadcast-quality Audio

Audio information is used as supplementary evidence in video surveillance applications. This HDCVI camera transmits audio signals over the coaxial cable, eliminating the need for separate audio wiring. In addition, the camera uses unique audio processing and transmission technology that eliminates noise to best duplicate source audio, guaranteeing high-quality and highly effective audio information.

Multiple-format Support

The camera supports multiple video formats including, HDCVI, CVBS, AHD, and TVI. The camera can switch between these four formats via the OSD menu or the switch located on the video output cable, making the camera compatible with not only HDCVI DVRs but also most existing HD/SD DVRs.

True Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Advanced 3DNR

3DNR is noise reduction technology that detects and eliminates random noises by comparing two sequential frames. Dahua's advanced 3DNR technology delivers remarkable noise reduction with little impact to sharpness, especially under limited lighting condition. 3DNR, in addition, effectively decreases the bandwidth and saves storage space.

Protection

The camera complies with the IK10 Vandal Resistance impact rating making it capable of withstanding the equivalent of 5 kg (11.02 lbs) of force dropped from a height of 40 cm (15.75 in.). Subjected to rigorous dust and water immersion tests and certified to the IP67 Ingress Protection rating makes it suitable for demanding outdoor applications. The camera allows for $\pm 30\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications, and its 4KV lightning rating provides effective protection for both the camera and its structure against lightning.

Technical Specification

Camera

| | |
|--------------------------|------------------------------------------------------|
| Image Sensor | 1/2.8-in. STARVIS™ CMOS Sensor |
| Effective Pixels | 2592 (H) x 1944 (V), 5 MP |
| Scanning System | Progressive |
| Electronic Shutter Speed | 1/3 s to 1/100,000 s |
| Minimum Illumination | Color: 0.005 lux at F1.3, 30 IRE 0 lux with IR on |
| S/N Ratio | More than 65 dB |
| IR Distance | Up to 30.0 m (98.43 ft) |
| IR On/Off Control | Auto, Manual |
| IR LEDs | Two (2) |

Lens

| | |
|----------------------|----------------------------|
| Lens Type | Motorized Lens, Fixed Iris |
| Mount Type | Board-in |
| Focal Length | 2.7 mm to 13.5 mm |
| Maximum Aperture | F1.3 |
| Angle of View | Horizontal: 102° to 29° |
| Focus Control | Auto, Manual |
| Close Focus Distance | 200 mm (7.87 in.) |

Installation Angle

| | |
|-------|------------------------------------------------------------|
| Range | Pan: 0° to 355° Tilt: 0° to 75° Rotation: 0° to 355° |
|-------|------------------------------------------------------------|

DORI Distances¹

| | Detect (8 ppf) | Observe (19 ppf) | Recognize (38 ppf) | Identify (76 ppf) |
|------|-------------------|---------------------|-----------------------|----------------------|
| Wide | 64 m (210 ft) | 26 m (85 ft) | 13 m (43 ft) | 6 m (20 ft) |
| Tele | 222 m (728 ft) | 89 m (292 ft) | 44 m (144 ft) | 22 m (72 ft) |

Video

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Maximum Resolution | 5 MP (2592 x 1944) |
| Frame Rate | 5 MP at 20 fps, 4 MP at 30 fps, 1080p at 30 fps |
| Video Output | One (1) BNC HDCVI High-definition Channel or, One (1) BNC CVBS Channel, switchable |

| | | |
|---------------------------------|-------------------------------|------------------------------------------------------------------------------------|
| Video Transmission ² | RG-59/U Coax | 720p: 800 m (2624.67 ft) 1080p: 500 m (1640.42 ft) 4 MP: 500 m (1640.42 ft) |
| | RG-6/U Coax | 720p: 1200 m (3937.01 ft) 1080p: 800 m (2624.67 ft) 4 MP: 700 m (2296.59 ft) |
| | CAT 6 UTP (balun required) | 720p: 450 m (1476.38 ft) 1080p: 300 m (984.25 ft) 4 MP: 300 m (984.25 ft) |
| Day/Night | Auto (ICR), Manual | |
| OSD Menu | Multi-language | |
| BLC Mode | BLC, HLC, True WDR | |
| WDR | 120 dB | |
| Gain Control | AGC | |
| Noise Reduction | 2D, 3D | |
| White Balance | Auto, Manual | |
| Smart IR | Auto, Manual | |

Certifications

| | |
|-------------------------------------|--------------------------------------------------|
| CE | EN55032 EN55024 EN50130-4 |
| Safety | UL60950-1 CAN/CSA C22.2 No.60950-1 |
| Electromagnetic Compatibility (EMC) | FCC CFR 47 Part 15 subpart B, ANSI C63.4-2014 |

Interface

| | |
|-------|----------------------------------|
| Audio | Input: One (1) Channel, RCA Jack |
|-------|----------------------------------|

Electrical

| | |
|-------------------|--------------------------------|
| Power Supply | 24 VAC ± 30% or 12 VDC ± 30% |
| Power Output | 12 VDC, 2 W Maximum |
| Power Consumption | Maximum 11.8 W (12 VDC, IR on) |

Environmental

| | |
|----------------------|------------------------------------------------------------------------------------------------------|
| Operating Conditions | -30° C to +60° C (-22° F to +140° F) Less than 90% RH *Initiate start up above -30° C (-22° F) |
| Storage Conditions | -30° C to +60° C (-22° F to +140° F) Less than 90% RH |
| Ingress Protection | IP67 |
| Vandal Resistance | IK10 |

Construction

| | |
|--------------|------------------------------------------------|
| Casing | Aluminium |
| Dimensions | ø122.0 mm x 88.90 mm (ø4.80 in. x 3.50 in.) |
| Net Weight | 0.48 kg (1.05 lb) |
| Gross Weight | 0.65 kg (1.43 lb) |

1. The DORI distance is a measure of the general proximity for a specific classification to help pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4, the standard that defines the criteria for the Detect, Observe, Recognize and Identify classifications.

2. Transmission distance results verified by real-scene testing in Dahua's test laboratory. Actual transmission distances may vary due to external influences, cable quality, and wiring structures.

Ordering Information

| Type | Part Number | Description |
|-----------------------|-----------------------------|----------------------------------------------------------------------------------------|
| 5 MP HDCVI Camera | A52AM9Z-B | 5 MP Starlight HDCVI 2.7 mm to 13.5 mm Vari-focal Lens IR Dome Camera, True WDR, Black |
| Accessories, optional | PFA106 | Mount Adapter |
| | PFA137-B | Junction Box, black |
| | PFA151-B | Corner Mount, black (Use with PFB305W wall mount) |
| | PFA152-E-B | Pole Mount, black (Use with PFB203W-B wall mount) |
| | PFA200W | Sun/Rain Shield (Use with PFB203W-B wall mount) |
| | PFB200C | In-ceiling Mount |
| | PFB203W-B | Wall Mount, black (Use alone or with PFA152-E-B pole mount) |
| | PFB220C | Ceiling Mount (Use with PFA106 mount adapter) |
| | PFB305W | Wall Mount (Use with PFA106 mount adapter) |
| | DH-PFM320D-US | 12 VDC, 2 A Power Adapter |
| | DH-PFM321D-US | 12 VDC, 1 A Power Adapter |
| | PFM800-4K | 4K Passive HDCVI Balun |
| | Audio Accessories, optional | HAP100 |
| HAP200 | | High-fidelity Pickup |

Accessories

Optional:



| Junction Mount | In-ceiling Mount |
|----------------------------|----------------------------|
| PFA137-B | PFB200C |
| | |
| Wall Mount | Pole Mount |
| PFB203W-B | PFB203W-B + PFA152-E-B |
| | |
| Wall Mount with Rain Shade | Ceiling Mount (Extensible) |
| PFA137+PFA200W | PFA106+PFB220C |
| | |
| Pole Mount with Rain Shade | |
| PFA137+PFA200W+PFA152-E | |
| | |

Dimensions (mm/in.)

