

## 49" Full-HD LCD Monitor



### ProductFeatures

- Industrial level DID LCD panel, suitable for extensive 7\*24 continuous works.
- High fidelity digital processing, brilliant and vivid video.
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Infrared, RS232 double mode, supporting remote PC control
- Brightness smart detection, power-saving
- Using Tamper-proof metal housing, no radiation
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Fast stack installation, professional project design, supporting arc-shaped mounting

### Technical Specifications

<b>Model</b>	<b>DHL49</b>	
<b>System</b>		
Diagonal	49"(16:9)	
Resolution	1920×1080 (FHD)	
Backlight	LED	
Brightness/Luminance (Standard)	450 cd/m <sup>2</sup>	
Contrast	1100:1	
Angle of view	178° /178° (vertical/horizontal)	
Response time	5.8ms	
<b>Signals</b>		
<b>Input</b>	<b>standard</b>	VGA(D-Sub)×1、 CVBS(BNC)×2、 DVI-D×1、 HDMI×1、 RS232×1、 USB×1
	<b>optional</b>	audio×1、 RJ45×1、 HDCVI×1、 SDI×1、 DP

		×1
<b>Output</b>	<b>Standard</b>	CVBS(BNC)×2、 RS232×1
	<b>optional</b>	audio×1、 DP×1
<b>General</b>		
Consumption (Standard)	60W	
Consumption (Standby)	≤1W	
Power Supply	AC100~240V (+/-10%),50/60 Hz	
Gross Weight	15kg	
Monitor dimensions	1127.1×667.3×52.9mm	
Work Environment	Temperature: 0℃~50℃	
	Humidity: 20%~90%	
<b>Accessory</b>		
<b>Standard</b>	<b>VGA cable, power cable</b>	
<b>Optional</b>	<b>Pedestal, hanging bracket</b>	

\*Design and specifications are subject to change without notice.

## Dimensions

