

# HDMI to HDCVI Converter



- One (1) HDMI Video Input, One (1) HDCVI Video Output (self-adaptive)
- Fully-enclosed, Dust-proof Design
- 10.2 Gbps Transmission Rate

## Technical Specifications

Physical Ports	Input: One (1) HDMI Output: One (1) BNC (HDCVI)
Port Specification	HDMI A Type
HDMI Version	HDMI 1.3, Backward compatible
HDMI Signal Format	EIA/CEA-861D Standard
Maximum Transmission Rate	10.2 Gbps
Input/Output TMDS Signal	0.5 to 1.5 Vp-p
Input/Output DCC Signal	5 Vp-p (TTL)
Output Level	1 Vp-p
HDMI Input Formats	1024 x 768 at 60 Hz, 1280 x 720 at 50/60 Hz, 1280 x 1024 at 60 Hz, 1600 x 1200 at 60 Hz, 1920 x 1080 at 50/60 Hz
HDCVI Output Formats	720p at 50 fps, 720p at 60 fps, 1080p at 25 fps, 1080p at 30 fps
Output Cable Length (75-5 Coaxial Cable)	1080p: 300.0 m (984.25 ft) 720p: 500 m (1640.42 ft)
Output Impedance	75 Ω
Video Bandwidth	45 MHz
Indicators	Power Video Alarm
Power Supply	12 VDC
Power Consumption	≤ 5 W
Working Temperature	-10° C to 55° C (14° F to 131° F)
Working Humidity	10% to 90%
Dimensions (W x D x H)	104.60 mm x 96.20 mm x 29.50 mm (4.11 in. x 3.79 in. x 1.16 in.)
Weight	0.315 kg (0.70 lbs)
Installation Method	Wall-mount