

16-port Managed PoE Switch

Layer 2 Gigabit PoE Switch



- Layer 2 Network Management PoE Switch
- Supports the IEEE802.3af and the IEEE802.3at Standards
- Supports Spanning Tree Protocol STP/RSTP
- Conforms to the IEEE802.3, IEEE802.3u, IEEE802.3ab/z and the IEEE802.3X Standards
- Supports One-key Recovery of IP Addresses and User Passwords

System Overview

The DH-PFS4220-16P-250 is a 16-port managed PoE Ethernet switch, which supports the IEEE802.3 af/at standards. The switch also supports Layer 2 network management and PoE management and provides high-speed data forwarding.

Technical Specification

Ethernet Ports	Two (2) 10/100/1000 Base-T Ports Two (2) 1000 Base-X Ports 16 10/100/1000 Base-T Ports (PoE Power Supply)
PoE Power Consumption	Each port: ≤ 30 W, Total: ≤ 250 W
PoE Protocol	PoE (IEEE802.3af), PoE+ (IEEE802.3at)
Switching Capacity	24.8 Gbps
Packet Forwarding Rate	8.33 Mpps
Power Requirements	100 VAC to 240 VAC
Working Temperature	-10° C to 55° C (14° F to 131° F)
Application Humidity	10% to 90%
Lightning Protection	Common Mode: 2 KV Differential Mode: 1 KV
Operating Temperature	-10° C to 55° C (14° F to 131° F)
Dimensions (W x D x H)	442.0 mm x 263.0 mm x 44.5 mm (17.40 in. x 10.35 in. x 1.75 in.)
Weight	3.54 kg (7.80 lb)

Service Specification

System	Username/Password: admin/admin
	IP Address: 192.168.1.200/24
PoE Budget	250 W
MAC Table Size	16K
VLAN	Port-based VLAN 802.1Q Standard LAN
Spanning Tree	STP, RTSP
Port Aggregation	Link Aggregation
Port Mirroring	Many-to-One Port Mirroring
Flow Control	Half-duplex based on back pressure type control Full Duplex based on PAUSE Frame
Multicast	IGMP Snooping
Security Features	Hardware Supports IP+MAC Binding based on port
	Support IEEE802.1x port authentication
System Maintenance	Configuration file upload/download
	Updated packet upload
	System logs
Network Management	Web (HTTP and HTTPS protocols)

Ordering Information

Type	Part Number	Description
PoE Switch	DH-PFS4420-16GT-250	Layer 2, 16-port Managed PoE Switch
	PFT3950	1.25 G, 850 nm, 500 m, LC, Multi-mode
	PFT3960	1.25 G, 1310/1550 nm, 20 km, LC, Single-mode
Accessories	PFT3970	1.25 G, 1550/1310 nm, 20 km, LC, Single-mode