




Smart Professional Surveillance System (SmartPSS) is a management software grants you access to all Dahua security products. SmartPSS is widely used with most Dahua surveillance and intercom/access systems in small to medium projects. SmartPSS maintains easy usability as well as great functionality. Monitoring, reviewing footage, smart search, intelligent alarms, smart tracking, every functionality is there for you for free.



Features



- The configurations of access control are newly supported in V2.02.1.
- Advanced E-map features are newly supported in V2.02.0.
- Support IPC, PTZ, NVR, EVS, HCVR, NVS, NKB VDP, Access Control and etc.
- Support up to 4 x 64 live view channels, main or sub streams optional.
- Support 4K cameras.
- Support H.265 streams.
- Support IPv6 devices.
- Support Windows XP/7/8/10.
- Support Smart Track by linking a fisheye and PTZ.
- Support Smart Track by linking a bullet and PTZ.
- Support multiple tour tasks.
- One channel can be split into different windows.
- Multiple channels can be previewed in channel zero.
- Auto find/import/export supported.
- Easy to manage up to 64 devices or 256 channels.
- Up to 36 channels synchronous playback.
- Time bar and events playback modes available.
- Support joystick to control PTZ cameras.
- Support fisheye camera Virtual PTZ operation by mouse.
- Alarm can be triggered via different events including IVS.
- Support e-map, you can clearly view and manage all device locations.
- PC-NVR enables local storage recording.
- TV wall configuration and control.
- Account management supported; and different users share different privileges.
- Log for event and user activities.
- Friendly GUI for an easy operation.
- Support P2P devices.
- Support fisheye image correction in both live viewing and playback.



Specifications

Version	Windows Version 2.02.0	MAC Version 2.00.0	
Device to Use			
Supported Devices	HCVR, NVR, IPC, PTZ, NVS, EVS,	DVR, NVR, IPC, PTZ, NVS, EVS,	
	NKB, VDP, Access Control and etc.	NKB and etc.	
Management Devices	Max 64	Max 50	
Management Channels	Max 256	Max 1024	
Device Management	Auto find, Add, Delete, Device group, Reboot, Setup, Specify netwo		
	segment.		
Health Report	Device status, Alarm info, HDD info		
Live Preview			
Video Display Split	1 / 4 / 6 / 8 / 9 / 16 / 25 / 36 or customized split for all versions		
	64 is only available for windows version		
Max Preview Screen	4	1	
Features	Snapshot, Record, Audio, Talk,	Snapshot, Record, Audio, Talk,	
	Instant playback, E-PTZ, Tours,	Instant playback, E-PTZ, Tours,	
	Views, Fisheye correction, IVS,	Views, Stream types, Channel	
	Stream types, Channel Zero,	Zero, Adjustable aspect ratio	
	Adjustable aspect ratio		
PTZ Control	Directions, PTZ, Focus, Iris, Preset, Tour, Pattern; Joystick control		
Alarm output control	Support		
Recording			
PC-NVR	32 Channels, 2TB each partition	Connects window's PC-NVR	
Record Mode	Manual, Schedule(Regular, MD, Alarm),Stop		
Playback			
Video Source	Local PC (Manual record or alarm record), Device itself, PC-NVR		
Picture Source	Local PC (Manual Snapshot), Device itself		
Max Channels	36	36	
Duration	24h for one search		
Search Type	Certain time, Motion detection, Alarm, Smart search, Call ID		
Max task of Export	10 once		
Features	Snapshot, E-PTZ, Audio, Speed	Snapshot, E-PTZ, Audio, Speed	
	1/8x~8x,Faster/Slower play,	1/8x~8x,Faster/Slower play,	
	Synchronization playback, Fisheye	Synchronization playback,	
	correction, Adjustable aspect ratio	Adjustable aspect ratio	
Export	Export as .dav/.avi/.mp4/.asf	Export as .dav	
Alarm Signal Monitori	ng		
Features	Schedule alarms, Setup actions, Operate/Memo alarm		
Alarm Type	External alarm, Video loss, Motion, Tampering, IVS events, HDD events		
Actions	Trigger recording, PTZ movement, Alarm, Popup video		
Е-Мар			
Number of Maps	Map group : Unlimited, Sub-Map, Layout : 64		
Image Format	JPEG / BMP		
Other Features			



PC-NVR	32 channels record		
Device Configure	Network, Encode, PTZ, Image,	Event, Record, Disk, Account,	
	Maintenance, Web		
Display	Remote control device's front panel screens		
Account	User and role management; privileges according to module & device		
Log	Client log, Remote device log, Operation log, System log, Alarm log		
Video Talk	Preview, Talk, Unlock, Call, Record, Announcement, Snapshot, Config		
System And OS			
System Requirement	CPU: Intel i3 or above;		
	Memory: 2G or above;		
	HDD: 80G or above		
OS	Window XP or above	OS 10.7 or above	
Display resolution	1024 x 768 or above		
Languages	26 languages	Chinese, English	
Performance is highly dependent on PC capacity, and the recommended configuration is just for reference.			

*Design and specifications are subject to change without notice.

 $\ \ \, \mathbb{C}$ 2015 Dahua Vision Technology Co., Ltd.

Contact us

Zhejiang Dahua Technology CO.,LTD.

A17, No.1199 Bin'an road, Binjiangdistrict, Hangzhou

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com